

POWERFUL. EFFECTIVE. READY TO USE.

The LetterPro is a complete platemaking system especially designed for water-washable letterpress plates. It encompasses the entire plate handling process including plate exposure, wash-out, drying and post-exposure.

All LetterPro functions are controlled by an integrated microprocessor. The touch-membrane keypad with digital display provides easy access to all parameters of the main equipment functions, and the ability to store nine different programs for individual plate types.

The LetterPro requires a minimum of maintenance and is the ideal solution for users with low-to-medium daily plate volume usage.



High power 40W UV-A lamps are used in both the main exposure and the post exposure section.



The dryer drawer provides drying functionality as well as post exposure.



Simple hardware controls and standard components require a minimum of maintenance effort.



The tank is designed with smooth walls only containing the heating element and a few sensors. This allows very easy cleaning of the tank.





Simple connection points at the back side of the unit.



The LetterPro is delivered with a flat brush. The brush is mounted on springs in order to secure an even brush pressure for different printing plate thicknesses.



The plate holder is magnetic and rotating in both directions at a fixed speed. Optionally, a special plate holder can be delivered for film-based printing plates.



Glunz & Jensen (Headquarters) Selandia Park 1 4100 Ringsted, Denmark +45 5768 8181 gj@glunz-jensen.com

Glunz & Jensen (Ringe) Nordmarken 2 5750 Ringe, Denmark +45 6262 4165 gj@glunz-jensen.com

Glunz & Jensen (Milan) Via Alessandro Volta 28 20088 Rosate (MI), Italy +39 02 900 90 180 gj@glunz-jensen.com



	LetterPro	
MODEL	140 C	200 C
PERFORMANCE		
Plate types	Water-washable Letterpress plates, metal-based or film-based.	
Plate width (max)	500mm (19.7")	700mm (27.6")
Plate length (min)	350mm (13.8")	500mm (19.7")
Plate thickness	0,43mm (0.017") to 2,3mm (0.091")	
CONSUMPTION		
Power supply	1W+N+PE, 230VAC	
Power consumption	2,2kW	4kW
GENERAL		
Dimensions, equipment (LxWxH)	750 x 710 x 980mm (29.5 x 28 x 38.6")	1050 x 880 x 1040mm (41.3 x 34.6 x 41.1")
Weight, equipment	98kg (216lbs)	219kg (483lbs)
Dimensions, crate (LxWxH)	900 x 730 x 108mm (35.4 x 28.7 x 42.5")	1030 x 1100 x 1240mm (40.6 x 43.3 x 48.8")
Weight, equipment + crate	144kg (318lb)	287kg (633lb)
Tank volume	19,5 litres	50 liters
Options	Sticky plate holder for film-based printing plates. Special brush types on request.	

Note: Standard configurations may vary in the market. Specifications are subject to changes without prior notice.

Glunz & Jensen (Americas)

500 Commerce Drive Quakertown, PA 18951, USA +1 267 405 4000 gj-americas@glunz-jensen.com Glunz & Jensen (Asia) Suzhou, 215129 P.R. China +86 150 1890 1632 gj@glunz-jensen.com

Glunz & Jensen (Thetford) Unit 4-6, Napier Place Stephenson Way Industrial Estate Thetford, Norfolk, IP24 3RL, UK +44 1842 765128 gj@glunz-jensen.com